

Full Size Stock

- 1. Open to any North American 80 newner 8 or 6 cly. NO 4 WHEEL DRIVE, VANS, CONVERIBLES.**
- 2. Flammable Material.** Headliner, door pads and all other flammable material must be removed inside car the dash maybe left in.
- 3. Glass/Airbags.** All glass must be removed, All airbags must be removed.
- 4. One 12 volt battery.** must be moved to front passenger floor board and securely fastened in box /container clear of fuel lines.
- 5. GAS TANK.** Stock gas tank must be removed. Steel marine tank our racing fuel cell, must be securely fastend down in middle of back seat area.**NO RATCHET STRAPS. NO GAS TANK PROTECTORS OF ANY KIND.**
- 6. FUEL LINE.** All fuel line must be leak proof and should be run inside car.
- 7. HOOD,DOOR,TRUNKS,TAILGATES.** Must be fastened with wire, chain our Weld with 3x3 plates max thinness 3/16 **4 PLATES PER DOOR- TRUNK TAILGATES 5 PLATES MAX.** Door plate are optional. Hood may wired our bolted with ¾ bolts not to go pass upper rad support. Hood must have 6 inch open.**NO BOLTING OUR SEAM WELDING PANELS. ALL BODY PANLES MUST BE IN STOCK LOCATION. NO PRE BANDING ALLOWED HOOD MUST REMAIN OPEN FOR INSPECTION.**
- 8. FRONT BUMPER.** Must be stock 80s FULL SIZE BUMPERS. **NO HARD NOSING NO STUFFING FRAME ANY WHERE.** Bumpers must be bolt our may have 2inch wide strap weld 2inch on bumper and 2inch on frame can be done on top and bottom. **NO FRAME REPAIR ALLOWED**
- 9. TIRES AND SUSPENSION.** Tires must be P RATED AND LOW AGGRESSION NO SKID TIRES. SUSPENSION MOST REMAIN STOCK NO MODIFCATION OF ANY KIND.
- 10. SAFTEY BARS.** One bar our H bar musts be mounted in windshield. Post to post bar is allowed, halo bar may be bolted to post to post bar can not touch the inner rocker panel. **NO REAR WINDOW BAR.**
- 11. MOTOR SWAPS ARE ALLOWED:** FORD CARS RUNNING GM ENGINE. NO ENGINE PORTECTORS OFF ANY KIND. MOST HAVE STOCK FORD 8.8 REAR END WITH 28 SPLINE AXLES NO RACING AXLES OF ANY KIND. IF MOTOR SWAP CAR FINISH IN TOP 3 THE REAR END WILL BE CHECK

Mini Smash Rules

1. **Open to any North American 4 or 6 cly car with wheelbase 106 under.** NO ENGINE SWAPS, 4 WHEEL DRIVE, VANS CONVERIBLES.
2. **Flammable Material.** Headliner, door pads and all other flammable material must be removed inside car the dash maybe left in.
3. **Glass/Airbags.** All glass must be removed, All airbags must be removed.
4. **One 12 volt battery.** must be moved to front passenger floor board and securely fastened in box /container clear of fuel lines.
5. **GAS TANK.** Stock gas tank must be removed. Steel marine tank our racing fuel cell, must be securely fastend down in middle of back seat area.**NO RATCHET STRAPS. NO GAS TANK PROTECTORS OF ANY KIND.**
6. **FUEL LINE.** All fuel line must be leak proof and should be run inside car.
7. **HOOD,DOOR,TRUNKS,TAILGATES.** Must be fastened with wire, chain our Weld with 3x3 plates max thinness 3/16 **4 PLATES PER DOOR TRUNK,TAILGATES 5 PLATES MAX.** Door plate are optional. Hood may wired our bolted with ¾ bolts not to go pass upper rad support. Hood must have 6 inch open.**NO BOLTING OUR SEAM WELDING PANELS. HOOD MUST REMAIN OPEN FOR INSPECTION.**
8. **FRONT BUMPER.** Must be stock mini car rebar bumper only. NO FULL SIZE BUMPERS. **NO HARD NOSING NO STUFFING FRAME ANY WHERE.** Bumpers most be bolt our may have 2inch wide strap weld 2inch on bumper and 2inch on frame can be done on top and bottom. **NO FRAME REPAIR ALLOWED**
9. **TIRES AND SUSPENSION.** Tires must be P RATED AND LOW AGGRESSION NO SKID TIRES. **SUSPENSION MOST REMAIN STOCK NO MODIFCATION OF ANY KIND.**
10. **SAFTEY BARS.** One bar our H bar musts be mounted in windshield. Post to post bar is allowed, halo bar may be bolted to post to post bar **can not touch the inner rocker panel. NO REAR WINDOW BAR.**

TRUCK Rules

- 1. Any 80 newer ½ OR ¾ ton truck , suburban, astro van. NO HD TRUCKS. NO MOTOR SWAPS. 4X4 ALLOWED MUST PULL FRONT SHAFT MAKE 2 WHEEL DRIVE. NO SOILD FRONT AXLES. INDEPENDENT FRONT SUSPENSION ONLY**
- 2. Flammable Material.** Headliner, door pads and all other flammable material must be removed inside car the dash maybe left in.
- 3. Glass/Airbags.** All glass must be removed, All airbags must be removed.
- 4. One 12 volt battery.** must be moved to front passenger floor board and securely fastened in box /container clear of fuel lines.
- 5. GAS TANK.** Stock gas tank must be removed. Steel marine tank our racing fuel cell, must be securely fastend **8 INCH FROM THE FROM FRONT OF THE BOX AND BOLT TO THE FREAM OF TRUCK . EXTENDED CAB TRUCK TANK CAN BE MOUNTED IN REAR OF CAB. NO RATCHET STRAPS. NO GAS TANK PROTECTORS OF ANY KIND.**
- 6. FUEL LINE.** All fuel line must be leak proof and should be run inside car.
- 7. HOOD,DOOR,,TAILGATES.** Must be fastened with wire, chain our Weld with 3x3 plates max thinness 3/16 **4 PLATES PER DOOR -TAILGATES 6 PLATES MAX.** Door plate are optional. Hood may wired our bolted with ¾ bolts not to go pass upper rad support. Box maybe bolt to cab in 4 place with ¾ bolts. Hood must have 6 inch open.**NO BOLTING OUR SEAM WELDING PANELS. HOOD MUST REMAIN OPEN FOR INSPECTION.**
- 8. FRONT BUMPER.** Must be stock TRUCK bumper only. NO FULL SIZE BUMPERS. NO HARD NOSING NO STUFFING FRAME ANY WHERE. Bumpers must be bolt our may have 2inch wide strap weld 2inch on bumper and 2inch on frame can be done on top and bottom. NO FRAME REPAIR ALLOWED.
- 9. TIRES AND SUSPENSION.** Tires must be P RATED AND LOW AGGRESSION NO SKID TIRES. SUSPENSION MOST REMAIN STOCK NO MODIFCATION OF ANY KIND.
- 10. SAFTEY BARS.** One bar our H bar musts be mounted in windshield. Post to post bar is allowed, halo bar may be bolted to post to post bar. **WIRE OUR BAR MOST BE MOUNTED BEHIND DRIVE IN BACK WINDOW OPENING.**